



MAN BOON MANUFACTORY LTD.

PRODUCT TECHNICAL DATA SHEET

Product Code: **ALARM CABLE 4C**

Page: **1 of 1**

Part Number : **841582**

Version: **A0**

Date: **2011-11-22**

Dimensional Features


Material Breakdown

	Dimensional Features	Material Breakdown
Inner Conductor <A>	4 / 0.19(+/-0.008)mm×7	Stranded bare copper
Insulation	4 / 1.0(+/-0.10) mm	PVC insulation
Rip-cord<C>	Rip-cord	Rip-cord
Sheath<D>	3.3(+/-0.18)mm	PVC sheath

Electrical Characteristics

Cable Construction

Max.Conductor(A) DC Resistance at 20°C(Ω/100M)	< 10.43
Min.Insulation DC Resistance at 20°C (MΩ*M)	>200
Rated Temperature(°C)	60
Rated Voltage (V)	300



Physical Characteristics

Minimum Bending Radius(mm)	15XD
Conductor Elongation at Break(%)	>15%
Sheath Tensile Strength (N/mm ²)	10
Sheath Elongation at Break(%)	125%

*Remark: Please contact us if you have more requirements or specifications subject to change, or else in accordance with the standards. *



Man Boon Manufactory Ltd.
Unit5, 7/F Grandtech Centre, 8 On Ping St., Shatin, N.T., Hong Kong
Tel: 852- 2558 7578 Fax: 852- 28970314
email: info@manboon.com www.manboon.com



ISO 9001
File A8606



RoHS (2002/95/EC)
Compliant



SABS
APPROVED